

Development of an optimised tube liner for trenchless pipe rehabilitation

Motivation

For the rehabilitation of brittle and cracked sewers, so-called "tube liners" have been inserted or rolled up into these sewers and pipes for many years to avoid excavation work. The basic concept of the tube lining method is the insertion of a textile tube soaked with a resin and length and internal diameter (DN 50 to > DN 2000) of the selected section of the damaged pipe to be renovated via the manholes. In the sewer, the tube is pressed against the pipe wall by means of air or water pressure and cured by steam, warm water or UV light to form a liner. The textile tubes consist of non-woven fabrics, stitch-bonded nonwoven or knitted plush made of polyester fibres or fabrics as well as non-woven fabrics/composites made of glass fibres. The liner structures are usually additionally reinforced by inserted filaments or seams, since the pulling in or rolling up of the tubes results in high longitudinal forces.

The aim of the research project was the development of an improved tube liner system combining advantages of the systems available on the market as well as eliminating disadvantageous properties. Thus, we wanted to increase the force absorption in the longitudinal direction to optimise the use of materials and the pore volume of the textiles for the best possible impregnation with the resins and to improve the tightness of the liner and bendability without wrinkling. Due to adapted properties, the production should be more cost-effective.

Experimental

The solution of the project included the development of non-woven fabrics made of polyester fibres or fibre mixtures and their consolidation into stitch-bonded nonwovens of the type Kunit and Multiknit. The focus was on adapting the textile-physical properties to the intended use. An airtight and media-tight coating was applied so that the tube liner can be inserted into the pipes using the inversion procedure. Adapted UV-curable resin formulations were developed on the basis of acrylates.



Tube liner made-up (right) and resined as well as UV cured in a damaged sewer pipe (left)

Results

In this research project, various non-woven fabrics were produced from polyester fibre mixtures and processed into stitch-bonded nonwovens using the Kunit and Multiknit processes. The textiles were coated media-tight with silicone (knife coating) and thermoplastic polyurethane (extrusion coating, film lamination). A polyester acrylate-based formulation was developed for curing using UV LED lamps. The produced tube liners were characterised in particular by their high longitudinal strength and ability to bend (without wrinkling).

Acknowledgement

We would like to thank the Federal Ministry for Economic Affairs and Climate Action for funding the research project "Development of an innovative tube liner system" (Reg. No. 49MF200100) within the funding „FuE-Förderung gemeinnütziger externer Industrieforschungseinrichtungen – Innovationskompetenz (INNO-KOM) – Marktorientierte Forschung und Entwicklung (MF)“.

INNO-KOM

Supported by:



on the basis of a decision
by the German Bundestag